Laundry Aide

LAUNDRY AIDE
MANUFACTURING



CUSTOMIZED FACTORY

OEM & ODM ACCEPTABLE

PROJECT DESIGN

TECHNICAL SUPPORT

www.laundryaide.com

LAM

Laundry Aide

LAUNDRY AIDE
MANUFACTURING

COMMERCIAL LAUNDRY EQUIPMENT SERIES



SMART LAUNDRY SOLUTIONS
FOR A MORE SUSTAINABLE TOMORROW

www.laundryaide.com

LAM

Laundry Aide

LAUNDRY AIDE
MANUFACTURING




Commercial Soft Mounted Washer Extractor




Side View



Front View



Rear View



Top View



Perspective View


Item/Model	CW-16	CW-20	CW-25	CW-30
Capacity(mm)	16	20	25	30
Drum size(mm)	Ø700*425	Ø700*540	Ø800*505	Ø800*580
Washing/High spinning speed(rpm)	40/850	40/850	40/820	40/800
Motor power(kw)	2.2	2.2	3	4
Inverter power(kw)	3.7	3.7	3.7	5.5
Electric heating power(kw)	9	9	12	15
Steam consumption (kg/h) (electric heating without)	3	3.5	5	7
G force	283	283	300	285
Water inlet diameter	3/4"	3/4"	3/4"	1"
Steam inlet diameter (electric heating without)	1/2"	1/2"	3/4"	3/4"
Steam pressure(Mpa) (electric heating without)	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6
Inlet water pressure(Mpa)	0.2-0.4	0.2-0.4	0.2-0.4	0.2-0.4
Drain diameter(mm)	3"	3"	3"	3"
Machine depth(mm)	1005	1100	1100	1200
Machine width(mm)	890	890	1010	1010
Machine height(mm)	1485	1485	1585	1585
Door center ground clearance(mm)	836	836	890	890
Detergent pump size(mm)	10	10	10	10
Machine net weight	450	495	630	700
Power Source	1P/220V/50HZ, 3P/380V/50HZ	1P/220V/50HZ, 3P/380V/50HZ	3P/380V/50HZ	3P/380V/50HZ
Rated power(kw) (electric heating)	11	11	15	16

Laundry Aide


LAUNDRY AIDE
MANUFACTURING




Commercial Tumble Dryer




Side View



Front View



Rear View



Top View




Perspective View

Item/Model	CD-16	CD-20	CD-30	CD-60
Capacity(kg)	16	20	30	56
Drum Size(mm)	Ø800*640	Ø800*725	Ø900*850	Ø1160*955
Drive Motor Power(kw)	0.25	0.25	0.37	1.5
Fan Motor Power(kw)	0.55	0.55	1.1	1.5
Inverter Motor Power(kw)	0.75	0.75	0.75	1.5
Power Source	1P/220V/50HZ 3P/380V/50HZ	1P/220V/50HZ 3P/380V/50HZ	3P/380V/50HZ	3P/380V/50HZ
Electric heating power(kw)	10.8	12	21	36
Gas consumption(kg/h) (electric heating without)	0.8	0.8	1.5	3
Exhaust outlet(mm)	160	160	200	240
Exhaust air volume(m3/h)	1200	1200	1700	2500
Door center ground clearance(mm)	926	926	996	1176
Machine width(mm)	880	980	980	1230
Machine depth(mm)	850	935	1026	1410
Machine height(mm)	1657	1657	1778	2188
Machine net weight(kg)	200	220	260	580


Laundry Aide

LAUNDRY AIDE
MANUFACTURING


Commercial Stacked Washer & Dryer




Side View



Front View



Rear View



Top View



Perspective View




Item / Model	SWD-16	SWD-20
Washing Capacity(kg)	16	20
Drying Capacity(kg)	16	20
Washer Inner Drum Diameter(mm)	420	540
Washer Inner Drum Depth(mm)	800	800
Dryer Inner Drum Diameter(mm)	600	725
Power Source	1P/220V/50HZ, 3P/380V/50HZ	1P/220V/50HZ, 3P/380V/50HZ
Washing Speed(rpm)	40	40
Drying Speed(rpm)	45	45
Balancing Speed(rpm)	100	100
High Extracting Speed(rpm)	700	700
Washer Motor Power(kw)	2.2	2.2
Dryer Motor Power(kw)	0.37	0.37
Dryer Fan Motor Power(kw)	0.55	0.55
Washer Electric Heating Power(kw)	9	9
Dryer Heating Method	Electric/Gas	Electric/Gas
Dryer Electric Heating Power(kw)	220V/9KW, 380V/10.8KW	220V/9KW, 380V/10.8KW
Water Consumption(L)	210	240
Rated Installed Power(kw)	220V/18KW, 380V/22KW	220V/18KW, 380V/22KW
Dryer Exhaust Pipe Diameter(mm)	60	60
Cold water Inlet(mm)	20	20
Washer Drain Pipe Diameter(mm)	75	75
Door 1 Center Height(mm)	640	640
Door 2 Center Height(mm)	1672	1672
Width(mm)	882	882
Depth(mm)	1043	1168
Height(mm)	2101	2101
Net Weight(mm)	405	445


Laundry Aide

LAUNDRY AIDE
MANUFACTURING


Commercial Stacked Dryers




Side View



Front View



Rear View



Top View



Perspective View



Item/Model	SDD-16	SDD-20	SDD-25
Drying Capacity(kg)	16/16	20/20	25/25
Drying Speed(rpm)	45	45	42
Main Motor Power(kw)	0.3*2	0.3*2	0.55*2
Fan Motor Power(kw)	0.55*2	0.55*2	0.75*2
Power Source	1P/220V/50HZ 3P/380V/50HZ	1P/220V/50HZ 3P/380V/50HZ	3P/380V/50HZ
Dryer Heating Method	Electric/Gas	Electric/Gas	Electric/Gas
Electric Heating Power(kw)	12*2	12*2	21*2
Drying Gas Consumption(kg)	2.5	2.5	4
Rated Installed Power(kw)	19.5	19.5	45
Gas Pressure(mpa)	0.25-4	0.25-4	0.25-4
Gas Inlet Pipe Diameter(mm)	10	10	10
Exhaust Pipe Diameter(mm)	160	160	200
Door 1 Center Height(mm)	595	595	645
Door 2 Center Height(mm)	1615	1615	1765
Width(mm)	882	882	980
Depth(mm)	1031	1156	1200
Height(mm)	2044	2044	2245
Net Weight(kg)	260	300	390


Laundry Aide

LAUNDRY AIDE
MANUFACTURING


Dry Cleaning machine




Item/Model	DC-8	DC-10	DC-12
Capacity(mm)	8	10	12
Drum size(mm)	Ø520*315	Ø640*350	Ø640*400
Washing/High spinning speed(rpm)	40/990	40/990	40/990
Motor power(kw)	1.1	1.5	1.5
Total power(kw)	2	2.4	2.4
Machine depth(mm)	1080	1100	1100
Machine width(mm)	760	950	950
Machine height(mm)	1480	1550	1550
Machine net weight(mm)	350	435	450
Oil tank(L)	100	130	130
Power Source	1P/220V/50HZ	1P/220V/50HZ	1P/220V/50HZ




Side View




Front View




Rear View



Top View





Perspective View

Laundry Aide

LAUNDRY AIDE
MANUFACTURING

INDUSTRIAL LAUNDRY EQUIPMENT SERIES







SMART LAUNDRY SOLUTIONS
FOR A MORE SUSTAINABLE TOMORROW

www.laundryaide.com

LAM


Laundry Aide

LAUNDRY AIDE
MANUFACTURING


Industrial Soft Mounted Washer Extractor




Side View



Front View



Rear View



Top View



Perspective View




Item/Model	CW-60	CW-100
Capacity(mm)	58	95
Drum size(mm)	Ø1020*725	Ø1230*813
Washing/High spinning speed(rpm)	40/680	40/650
Motor power(kw)	5.5	7.5
Inverter power(kw)	7.5	11
Electric heating power(kw)	36	48
Steam consumption (kg/h) (electric heating without)	20	30
G force	279	291
Water inlet diameter	1 1/2"	1 1/2"
Steam inlet diameter (electric heating without)	1"	1"
Steam pressure(Mpa) (electric heating without)	0.4-0.6	0.4-0.6
Inlet water pressure(Mpa)	0.2-0.4	0.2-0.4
Drain diameter(mm)	Ø140	Ø140
Machine depth(mm)	1710	1965
Machine width(mm)	1610	1750
Machine height(mm)	1915	2040
Door center ground clearance(mm)	1045	1130
Machine net weight(mm)	2200	3200
Power Source	3P/380V/50HZ	3P/380V/50HZ
Rated power(kw) (electric heating)	42	56


Laundry Aide

LAUNDRY AIDE
MANUFACTURING


Industrial Soft Mounted Washer Extractor




Side View




Front View



Rear View



Top View



Perspective View



Item/Model	XGQ-50	XGQ-70	XGQ-100
Capacity(mm)	50	70	100
Drum size(mm)	Ø1080*625	Ø1080*725	Ø1230*800
Washing/High spinning speed(rpm)	40/680	40/680	40/650
Motor power(kw)	5.5	5.5	7.5
Inverter power(kw)	7.5	7.5	11
Electric heating power(kw)	36	36	48
Steam consumption (kg/h) (electric heating without)	20	20	30
G force	279	279	291
Water inlet diameter	1 1/2"	1 1/2"	1 1/2"
Steam inlet diameter (electric heating without)	1"	1"	1"
Steam pressure(Mpa) (electric heating without)	0.4-0.6	0.4-0.6	0.4-0.6
Inlet water pressure(Mpa)	0.2-0.4	0.2-0.4	0.2-0.4
Drain diameter(mm)	Ø140	Ø140	Ø140
Machine depth(mm)	1710	1810	1965
Machine width(mm)	1610	1610	1750
Machine height(mm)	1915	1915	2040
Door center ground clearance(mm)	1045	1045	1130
Machine net weight(mm)	2200	2350	3200
Power Source	3P/380V/50HZ	3P/380V/50HZ	3P/380V/50HZ
Rated power(kw) (electric heating)	42	42	56

Laundry Aide


LAUNDRY AIDE
MANUFACTURING




Industrial Soft Mounted Washer Extractor




Side View




Front View



Rear View



Top View



Perspective View


Item/Model	XGQ-120	XGQ-130	XGQ-150	XGQ-200
Capacity(mm)	120	130	150	200
Drum size(mm)	Ø1300*900	Ø1300*980	Ø1470*885	Ø1600*1000
Washing/High spinning speed(rpm)	32/670	32/670	32/650	32/630
Motor power(kw)	11	11	18	30
Inverter power(kw)	15	15	22	37
G force	270	268	265	260
Water inlet diameter	1 1/2″	1 1/2″	2″	2″
Steam inlet diameter	1″	1″	1 1/2″	1 1/2″
Steam pressure(Mpa)	0.4-0.6	0.4-0.6	0.4-0.6	0.4-0.6
Inlet water pressure(Mpa)	0.2-0.4	0.2-0.4	0.2-0.4	0.2-0.4
Drain diameter(mm)	160	160	160	160x2
Machine depth(mm)	2000	2100	2600	2650
Machine width(mm)	1840	1840	2133	2300
Machine height(mm)	2200	2200	2270	2300
Machine net weight(mm)	3900	3900	4500	9200
Power Source	3P/380V/50HZ	3P/380V/50HZ	3P/380V/50HZ	3P/380V/50HZ

Laundry Aide


LAUNDRY AIDE
MANUFACTURING




Industrial Tumble Dryer




Side View



Front View



Rear View



Top View



Perspective View

Item/Model	HG-50	HG-70	HG-100
Capacity(kg)	50	70	100
Drum Size(mm)	Ø1140*970	Ø1300*970	Ø1450*1190
Drive Motor Power(kw)	1.5	1.5	2.2
Fan Motor Power(kw)	1.5	1.5	1.5x2
Voltage(v)	380	380	380
Electric heating power(kw)	36	48	60
Gas consumption(kg/h) (electric heating without)	3	4	5
Exhaust outlet(mm)	290	290	350x280
Exhaust air volume(m3/h)	2500	3600	5000
Door center ground clearance(mm)	1176	1176	1310
Machine width(mm)	1240	1400	1620
Machine depth(mm)	1625	1625	1920
Machine height(mm)	1948	2110	2405
Machine net weight(kg)	580	720	1100
Power Source	3P/380V/50HZ	3P/380V/50HZ	3P/380V/HZ

Laundry Aide

LAUNDRY AIDE
MANUFACTURING

SHANGHAI LAUNDRY AIDE MACHINERY CO., LTD.

CONTACT US

NO. 251 FENGWANG ROAD,
FENGXIAN DISTRICT,
SHANGHAI,P.R.CHINA 201411

info@laundryaide.com

www.laundryaide.com

Phone/Whatsapp:
+86 15316836110
+86 17761960699

WHATSAPP

WHATSAPP

WECHAT

LAM